Rescue Sled



The RS Series Rescue Sleds are flood water rescue craft for inshore crisis rescues and flooded urban and coastal areas. The Rescue sled is available in seven standard sizes 3, 5, 6, 10 & 15 man. The 3, 5 & 6 person sleds are ideal for swift-water and narrow access rescue.

The 10 & 15 person sleds have a larger floor space and load capacity which are more suited for emergency evacuation situations. The RS10T & RS15T are fitted with a transom allowing them to be used with a small outboard motor even in shallow waters.

- Lightweight and easily portable
- Easy to maneuver
- Can be paddled or pulled by hand
- Exceptionally Stable
- · Can be used in shallow water
- Open low stern makes casualty recovery easier
- Easily used by wheelchair users
- Exceptionally tough and durable

- · Rapid inflation and deployment
- Easily launched into the surf zone for sea rescue, with a raised bow for improved performance in waves
- Open stern for easy access and self-bailing
- Minimal training, servicing and maintenance costs
- Individuals can sit on the floor surrounded by the inflated tubes, offering a comfortable and reassuring rescue environment

Used For:

Crisis rescue

- River rescue
- Flooded coastal and urban areas
- Casualty recovery
- Shallow water rescue

Flood rescue	 Flooded coastal and urban areas 				Shallow water rescue		
Technical Data	RS3	RS5	RS6	RS10	RS15	RS10T	RS15T
Product Code	WR0001	WR0002	WR0169	WR0194	WR0005	WR0004	WR0006
No. Of Persons	3	5	6	10	15	10	15
O.A Length (cm)	256	331	397	400	520	400	520
O.A Width (cm)	117	117	117	190	235	200	217
O.A Height (cm)	40	40	40	56	77	71	71
Floor Thickness (cm)	12.5	12.5	12.5	12.5	12.5	12.5	12.5
Tube Diameter Bow/Stern (cm)	15/23	15/23	15/23	35/23	46/23	48/23	48/23
Max. Load (kg)	240	400	480	800	1200	800	1200
Working Pressure	0.2	0.2	0.2	0.2	0.2	0.2	0.2
No. Of chambers	2	2	2	4+floor	4+floor	4+ floor	4+floor
Air Requirements (ltr)	530	670	710	2000	3800	2900	3500
Pack Size (cm)	88x35x30	88x35x30	88x35x30	88x55x35	90x70x52	140x50x35	165x55x35
Est.Weight (kg)	17	19.5	20.5	35	46	48	60
Recommended Regulator	8 Bar	8 Bar	8 Bar	8 Bar	8 Bar	8 Bar	8 Bar

Rescue Sled





Optional Equipment on Page 38

